

JACOBSEN[®]

A Textron Company

JACOBSEN[®] HR[™] -6010



**The best of both worlds.
A high production rotary with a 10' 7" wide cutting path with a
narrow, 61-inch transport and storage width.**

JACOBSEN® HR™- 6010

POWERTRAIN

Engine	Liquid-cooled Perkins® 4-cylinder Turbo Charged diesel
Power	60 hp (44 kW) @ 2800 rpm
Displacement	135.2 cu in (2213 cc)
Cooling System	1.3 gal (4.9 l) capacity
Oil Capacity	8.7 at (8.2 l)
Fuel Capacity	17 gal. (45.6 l) High Density polyethylene tank; 10-micron in-line prefilter and canister filter
Hydraulic System and Fluid	5 gal (19 l); 10-micron filter and test ports; 10W-30
Transmission	Servo Controlled variable displacement hydraulic pump directly mounted to engine
Drive	Full-time four-wheel drive; two-wheel drive for transport
Electrical	12-volt automotive battery with 40 amp alternator
Tires	
Front	24 x 13-12 tubeless turf
Rear	20 x 10-8 tubeless turf
Ground Pressure	14 psi
Operating Speeds	
Transport (in two-wheel drive)	14 mph (22.5 km/h)
Mowing	7 mph (11 km/h)
Reverse	4 mph (7 km/h) max.

OPERATOR COMFORT, SAFETY AND CONTROL

Throttle	Console-mounted lever
Brakes	Hydrostatic through traction drive
Parking Brake	Wed hydraulic disc brakes; hand lever
Speed Control	Foot-pedal variable forward/reverse speeds Individual mow & transport positions
Console Gauges	Water temperature, fuel, oil pressure warning, hydraulic oil temperature, glow-plug indicator, alternator lamp, hour meter
Operator Controls	Throttle, Two-wheel/four-wheel drive, PTO on/off, horn, engine start; 3-individual deck Lift levers; wing deck latches
Deck Lift/Lower	Rocker switch
Steering	Hydrostatic power steering to rear wheels; w/tilt steering wheel
Seat	Vinyl-covered, high-back, height, back/forward adjustments
Entry/Exit Steps	Left/right steps for safe cockpit entry and exit

MOWERS

Cutting Width	127 in
Cutting Height	Operator-adjustable from 1 in. to 4.75 in.
Cutting Speed	7 mph (11 km/h)
Deck Construction	10-gauge steel with welded, 7-gauge deck skirts; 1-in round steel reinforcement wrap
Deck Drive	Single L-L poly section belt
Deck Lift Positions	
Center Deck	6 in. lift for transport
Wing Decks	Individual controls with full lift and lock to vertical for transport/storage
Productivity	6.8 acres/hr. (2.8 ha/hr) at 7 mph (11 km/h)
Deck Cutting Width	
Center Deck	60 in
Wing Decks	40.5 in (103 cm)
Overall Cutting Width	127 in (3.23 m)
Blades	Seven; 21 in (53 cm) heat treated
Spindles	1.25 in (3.2 cm) diameter w/double-sealed bearings
Anti-Scalp Rollers	
Center Deck	Three front; two rear
Wing Decks	Optional
Wheels	
Center Deck	Two 11 x 4.0 foam filled tires
Each Wing Deck	Two 9 x 3.5 foam filled tires
Weight Transfer System	Patented system: transfers up to 200 lbs. from mowing decks to tractor for improved stability and traction
DIMENSIONS	
Transport Width	61 in. (155 cm)
Height	53 in. (135 cm)
Length with Decks	122 in. (310 cm)
Weight with Decks	3,476 lbs. (1577 kg)
Operator Sound Level	92 dB(A) at 2,800 rpm
Certifications	ANSI B71.4-1990 Safety Standards European Community Directives and Amendments

Options: Two-post ROPS, lighting kit (front and rear lights, brake lights and four-way flashers)