



## Verti-Drain® 7521

### Specifications

Sku	: 7521
Working width m	: 2.1 m
Working width inch	: 83 inch
Max working depth mm	: 400 mm
Max working depth inch	: 16 inch
Working speed at hole spacing 65 mm km/h	: 0.70 km/h
Working speed at hole spacing 2-12 mph	: 0.45 mph
Weight kg	: 1375 kg
Weight lbs	: 3025 lbs
Hole distance with 12 mm tines mm	: 65 mm
Hole distance with 12 x 6 tines inches	: 2.5 inch
Hole distance with 24 mm tines mm	: 129 mm
Hole distance with 1 x 16 tines inches	: 5 inch
Hole spacing driving distance direction mm	: 50-195 mm
Hole spacing distance driving direction inches	: 2 - 7-1/2 inch
Max diameter-solid tine mm	: 24 x 400 mm
Max diameter-solid tine inches	: 1 x 16 inch
Max diameter hollow tine mm	: 32 x 300 mm
Max diameter hollow tine inches	: 1-1/4 x 12 inch
Min tractor hp required	: 55 HP
Min lifting capacity kg	: 1650 kg
Min lifting capacity lbs	: 3600 LBS
Max capacity with spacing 65 mm m2hr	: 1470 m <sup>2</sup> /hr
Max capacity with spacing 2-12 ft2hr	: 13400 ft <sup>2</sup> /hr
Three-pointhitch	: 3-point CAT 2
Rpm max	: 500 rpm
Gear case oil	: 80W90 - 5.8
Lubricant	: EP2
Dimensions mm	: 2280 x 1000 x 1500 mm
Dimensions inch	: 91 x 40 x 60 inch

### Components

Solid tines 18 x 300 mm (3/4 x 12") with adapters  
 3-speed gearbox  
 Front and rear roller  
 PTO  
 Toolbox with combi tool and manual

### Parts

Hollow tines