UNMATCHED LEFT SATILITY




- · 800 lb. (362.8 kg) total vehicle capacity
- Rustproof, aircraft-grade aluminum frame is stronger than competitors' steel frames and resists corrosion.
- 14-hp rated overhead cam engine with EFI (Electronic Fuel Injection) and side-entry fuel tank improves fuel efficiency by as much as 50%.
- Cockpit style interiors, ergonomic dash and improved hip restraints provide one-of-a-kind comfort.
- Integrated track attachment system, optional tool holders, bed dividers and cargo tie downs increase versatility and save bed space.

- Features ERIC[™], a solid-state, high frequency charger that boost charging efficiency by 10% and can be field-programmed through a USB port
- · The industry's longest and strongest warranty





CARRYALL 300	ELECTRIC	GASOLINE
Motor/Engine**	48-volt DC	Subaru, 4-cycle, OHC
Controller	250 Amp - Solid State	
Displacement	_	404 cc
Cylinders	_	Single
Valving	-	Overhead Cam
Cooling	-	Air Cooled
Horsepower (Rated)	3.3 hp (2.4 kW) rated; Peak 13 hp (9.6 kW)	14.0 hp (10.3 kW) rated @ 3600 RPM per SAE J1940
Max Torque	34.5 ft-lb (46.7 N-m) rated @ 1980 rpm	19.91 ft lb (27.0 N-m) rated @ 2400 RPM
Lubrication	-	Splash lubrication
Governor	-	Ground Speed
Transmission	Direct drive, double reduction helical gear	Continuously Variable Transmission (CVT)
Gear Selection	Forward/Neutral/Reverse	
Gear Ratio	12.32:1	11.47:1 forward;15.63:1 reverse
Ignition	-	Capacitive Discharge
Battery	Six 8-volt Flooded Lead Acid	12-volt 500 CCA 105 min Reserve
Charger	ERIC (650 W High Frequency)	-
Headlights	Two 37.5 Watt Halogen	
Fuel Delivery System	-	Electronic Fuel Injection (EFI)
Fuel Capacity	_	5.5 gal (20.8 L)
Steering Mechanism	Self-adjusting Rack and Pinion	
Suspension (Front)	Independent leaf spring with dual hydraulic shocks	
Suspension (Rear)	Semi-independent leaf spring with dual hydraulic shocks	
Brakes	Rear Mechanical Drum	
Park Brake	Foot Operated, Multi-lock	
Body (Front & Finish)	ArmorFlex with automotive paint/clearcoat	
Body (Frame & Rear)	Aluminum	
Tires (Front)	20 x 10-10, 6-ply, Premium Tread	
Tires (Rear)	20 x 10-10, 6-ply, Premium Tread	
Wheelbase	65.5 in (166.3 cm)	
Overall Height	47.1 in (119.6 cm)	
Overall Length	110.1 in (279.6 cm)	
Bed L x W x H (Cargo Box)	36.2 x 47.5 x 10.5 in (91.9 x 120.6 x 26.6 cm)	
Ground Clearance (Differential)	5.6 in (14.2 cm)	5.2 in (13.2 cm)
Track Width (Front)	36.6 in (·
Track Width (Rear)	39.5 in (100.3 cm)	
Max Width (w/o Mirrors)	50.3 in (127.7cm)	
Outside Clearance (Diameter)	230.5 in (585.4 cm)	
Curb Weight (with Batteries)	1105 lb (501.2 kg)	817 lb (370. 5 kg)
Total Vehicle Capacity	800 lb (3	362.8 kg)
Bed Load Capacity	300 lb (136.0 kg)	
Towing Capacity	800 lb (362.8 kg)	
Combined Gross Vehicle Capacity	800 lb (362.8 kg)	
Speed	5-17 mph (8-27 km/h)	15-17 mph (24-27 km/h)
Warranty	4 yr limited battery warranty 3 yr limited powertrain/frame 2 yr limited remaining vehicle	3 yr/3000 hr limited powertrain/frame 2 yr limited remaining vehicle









. 275.

Wheel Covers

Canopy Top





Brush Guard

Flatbed





Cargo Box

Stakeside Kit





Rear Receiver Hitch

Enclosed Cab





Range Cab

Body Colors



(S) Standard Color; (P) Premium Color