

The only people who will know you have rolled your greens, will be the players enjoying it.

Our whisper quiet 48v electric engine ensures you can prepare your greens while your neighbors sleep undisturbed, morning or night. Available in both lead acid or lithium powered.

Our intuitive quick release accessories let you easily change between slitting, spiking or brushing in seconds. No tools required.

The RE50 incorporates our patented self cleaning nodules. These remove clipping build up during rolling to eliminate

dumping and keep the smoothing rollers clean of debris for a smoother more even roll.

Our rollers are lighter, smarter, and more adaptable. Where other machines rely on weight to heavily compress the playing surface, our lightweight rollers create a smooth, true surface without compacting the soil beneath, resulting in better soil structure and healthier grass.

Contact your local dealer today to experience the results and features of not just any roller: the only roller officially endorsed by the US PGA for the result it delivers.





RELIABILE AND VERSATILE

The patented tri-roller smoothing heads are fitted with hassle free, self cleaning nodules to eliminate dumping and debris impact. Heavy duty sealed bearings, rubber cushion mounts and two greasing points help reduce maintenance requirements.

Our innovative range of optional, toolless attachments increase productivity, providing great results through design, not weight.



Changing attachments has never been so easy. Simply remove the quick release safety pin & switch out the attachment.









RE50 Specifications

Engine	
Type	48V AC Electric
Horsepower	18HP (13.5 kw)
Engine Cover	Fully enclosed
Battery	Lead Acid - Standard, Lithium - Optional
Transmission	
Manufacturer	Falk Ultramite
Type	Double reduction helical
Drive Train	Toothed belt
Drive Roller	Rubber coated, non-stick.
	Flexible, contour following
Direction Control	Fingertip switch
Speed Control	Progressive foot pedal movement, down/up
Operating Speed	0-9 mph (0-15kph)
Steering	Joystick - Light load, directly connected to smoothing head
Seat	Premium UV protected, with adjustable armrests
Trailer	Integrated, extra heavy duty, folds from rolling position to transport position
Ground Pressure (Footprint)	3.8 psi (26 kPa)

Smoothing Heads	2 overlapping, fitted with tri-rollers in each head, no gap between heads
Rolling Width (Swath)	50" (1270mm)
Weight	800 lb (364 kg)
Drawbar Lifting weight when connecting Ball style	25lb (11kg) Dual size 2″or 50mm
Tires	18 x 6.50 x 4. 4 ply
Engine Start/Stop	Recoil & Switch
Brake Roller	Regenerative - finger switch or foot pedal
Lights	AC/DC LED
Battery Charger	Universal 48V onboard (lithium & acid)
Optional Equipment Slicer - Quick release	15 blades, self-rotating on shaft & bearings Slice depth up to 7/8" (22mm)
Spiker - Quick release Brush - Quick release Drop down leg	30 wheels, self-rotating. SS shaft & bearings Spike depth ⁷ /8" (22mm) Stiff or Medium strength bristles available Suits Ball style drawbar only
Warranty	2 years - Limited manufacturer's warranty.