Verti-Drain® 7526

The Verti-Drain® 7526 offers width and depth in one machine, with the ability to work to 16" / 400mm deep over a 102" / 260cm width, it is ideal for the large open spaces including fairways, racetracks and larger sports fields.



Specifications

SKU	S0001507
Operation	Tractor Mounted
Working width (m)	2.6
Working width (inch)	102
Max. Working depth (mm)	400
Max. Working depth (inch)	16
Working speed at hole spacing 65 mm (km h)	0.7
Working speed at hole spacing 2 1 2 inch (mph)	0.45
Weight (kg)	1595
Weight (lbs)	3510
Hole distance with 12 mm tines (mm)	65
Hole distance with 1 2 x 6 inch tines (inch)	2.5
Hole distance with 24 mm tines (mm)	129
Hole distance with 1 x 16 inch tines (inch)	5
Hole spacing distance driving direction (mm)	50-195
Hole spacing distance driving direction (inch)	2 - 7-1/2
Max. Diameter solid tine (mm)	24 x 400
Max. Diameter solid tine (inch)	1 x 16
Max. Diameter hollow tine (mm)	32 x 300
Max. Diameter hollow tine (inch)	1-1/4 x 12
Min. Tractor HP required	65
Min. Lifting capacity 610 mm behind the lifting eyes (kg)	1900
Min. Lifting capacity 24 inch behind the lifting eyes (lbs)	4200
Max. capacity with spacing 65 mm (m^2 hr)	1820
Max. capacity with spacing 2 1 2 inch (ft^2 hr)	16600
Three-point hitch	3-point CAT 2
Rpm Max.	500
Gear case oil	Life time grease EPL 00
Lubricant	EP 2
Slip clutch setting	800 Nm

© 2026 Redexim